



YUXIANG

www.magnet-tech.com

T TYPE

(1) ORDERING CODE

R80 T 22.5 x 13.8 x 6.4


Material Type Outside Diameter(A) Inside Diameter Length(D)

Applications: EMI suppression generated form ribbon cable used in digital equipment.

Materials can be Changed according to your request



(2) SHAPE



(3) DIMENSIONS

NO.	TYPE	Dimensions(mm)		
		A	C	D
1	T2.54×1.27×0.8 core	2.54±0.20	1.27±0.20	0.80±0.20
2	T2.54×1.27×1.27 core	2.54±0.20	1.27±0.20	1.27±0.20
3	T4×2×1.5 core	4.00±0.20	2.00±0.20	1.50±0.20
4	T4.4×2.8×2.5 core	4.40±0.20	2.80±0.20	2.50±0.20
5	T4.4×3×1.2 core	4.40±0.20	3.00±0.20	1.20±0.20
6	T4.5×1.8×1.4 core	4.50±0.20	1.80±0.20	1.40±0.20
7	T4.5×2.2×0.75 core	4.50±0.20	2.20±0.20	0.75±0.20
8	T4.8×2.8×1.5 core	4.80±0.20	2.80±0.20	1.50±0.20
9	T6×3×2 core	6.00±0.20	3.00±0.20	2.00±0.20
10	T6×3×3 core	6.00±0.20	3.00±0.20	3.00±0.20
11	T8×4×3 core	8.00±0.20	4.00±0.20	3.00±0.20
12	T8×5×4 core	8.00±0.20	5.00±0.20	4.00±0.20
13	T9×5×3 core	9.00±0.20	5.00±0.20	3.00±0.20
14	T9×5×4.5 core	9.00±0.20	5.00±0.20	4.50±0.20
15	T9.5×5×5 core	9.50±0.20	5.00±0.20	5.00±0.20
16	T9.65×5.02×5 core	9.65±0.20	5.02±0.20	5.00±0.20
17	T9.65×6.35×4.8 core	9.65±0.20	6.35±0.20	4.80±0.20
18	T10×6×4 core	10.0±0.30	6.00±0.20	4.00±0.20
19	T10×7.1×5 core	10.0±0.30	7.10±0.20	5.00±0.20
20	T12×6×4 core	12.0±0.30	6.00±0.20	4.00±0.20
21	T12.7×7.9×6.35 core	12.7±0.30	7.90±0.20	6.35±0.20
22	T13×7×4 core	13.0±0.30	7.00±0.20	4.00±0.20
23	T13.3×7.2×3 core	13.3±0.30	7.20±0.20	3.00±0.20
24	T14×8×7 core	14.0±0.30	8.00±0.20	7.00±0.20
25	T14×9×5 core	14.0±0.30	9.00±0.20	5.00±0.20
26	T14×10×8 core	14.0±0.30	10.0±0.30	8.00±0.20
27	T15×8×6 core	15.0±0.30	8.00±0.20	6.00±0.20
28	T16×9×4 core	16.0±0.30	9.00±0.20	4.00±0.20

29	T16×10×5 core	16.0±0.30	10.0±0.30	5.00±0.20
30	T16×12×8 core	16.0±0.30	12.0±0.30	8.00±0.20
31	T17.5×13.2×7.7 core	17.5±0.30	13.2±0.30	7.70±0.20
32	T18×8×6.5 core	18.0±0.30	8.00±0.20	6.50±0.20
33	T18×9.5×3 core	18.0±0.30	9.50±0.20	3.00±0.20
34	T18×10×6 core	18.0±0.30	10.0±0.30	6.00±0.20
35	T18×10×10 core	18.0±0.30	10.0±0.30	10.0±0.30
36	T18.7×11×6.5 core	18.7±0.30	11.0±0.30	6.20±0.20
37	T19×10×10 core	19.0±0.30	10.0±0.30	10.0±0.30
38	T20×10×10 core	20.0±0.40	10.0±0.30	10.0±0.30
39	T20×11×10 core	20.0±0.40	11.0±0.30	10.0±0.30
40	T20×16×8 core	20.0±0.40	16.0±0.30	8.00±0.20
41	T20.4×10.3×10 core	20.4±0.40	10.3±0.30	10.0±0.30
42	T21×13.2×6.4 core	21.0±0.40	13.2±0.30	6.40±0.20
43	T22×13.5×6.4 core	22.0±0.40	13.5±0.30	6.35±0.20
44	T22.5×13.8×6.4 core	22.5±0.40	13.8±0.30	6.40±0.20
45	T23×12.5×9.5 core	23.0±0.40	12.5±0.30	9.50±0.20
46	T25×13×12 core	25.0±0.50	13.0±0.30	12.0±0.30
47	T25×15×12 core	25.0±0.50	15.0±0.30	12.0±0.30
48	T27×15×12 core	27.0±0.50	15.0±0.30	12.0±0.30
49	T28×16×13 core	28.0±0.50	16.0±0.30	13.0±0.30
50	T29×19×7.7 core	29.0±0.50	19.0±0.30	7.70±0.20
51	T30×18×7.5 core	30.0±0.50	18.0±0.30	7.50±0.20
52	T31×19×8 core	31.0±0.50	19.0±0.30	8.00±0.20
53	T31×19×10 core	31.0±0.50	19.0±0.30	10.0±0.30
54	T35×21×12 core	35.0±0.50	21.0±0.40	12.0±0.30
55	T36×23×12 core	36.0±0.50	23.0±0.40	12.0±0.30
56	T36×25×12 core	36.0±0.50	25.0±0.50	12.0±0.30

Copyright 2005 YUXIANG Magnetic Materials Ind. Co., Ltd. All Rights Reserved.

Add: 16F1, jinyuan building, NO.57, hubin S.Rd., Xiamen, China. 361004

Tel : (86)592 2225286 (86)592 2219816 (86)592 2217138 Fax: (86)592 2207122

Email : magnetcom@gmail.com sales@magnet-tech.com