



# YUXIANG

www.magnet-tech.com

China Professional Ferrite Core Supplier

## RID TYPE

### (1) ORDERING CODE

R120 RID 7.5 × 10.3 × 13.3 H4.0

Material    Type    Width(A)    Thickness(D)    Length(B)    Hole(c Φ)

Applications: Balun Transformers

Materials can be Changed according to your request



### (2) SHAPE




Fig 1




Fig 2




Fig 3




Fig 4

## (3)DIMENSIONS

| NO. | TYPE                  | Fig | Dimensions(mm) |            |            |            |
|-----|-----------------------|-----|----------------|------------|------------|------------|
|     |                       |     | A              | B          | C          | D          |
| 1   | RID2x1.5x3.5 H0.9     | 1   | 2.00 ±0.20     | 3.50 ±0.20 | 0.90 ±0.10 | 1.50 ±0.20 |
| 2   | RID2x2.8x5 H1.1       | 1   | 2.00 ±0.20     | 5.00 ±0.20 | 1.10 ±0.10 | 2.80 ±0.20 |
| 3   | RID2.3x5x7.5 H0.8     | 4   | 2.30 ±0.20     | 7.50 ±0.20 | 0.80 ±0.10 | 5.00 ±0.20 |
| 4   | RID2.4x2.65x H0.9     | 2   | 2.40 ±0.20     | 5.00 ±0.20 | 0.90 ±0.10 | 2.60 ±0.20 |
| 5   | RID2.6x2x5.3 H1.2     | 1   | 2.60 ±0.20     | 5.30 ±0.20 | 1.20 ±0.10 | 2.00 ±0.20 |
| 6   | RID3x3.5x6 H1.5       | 1   | 3.00 ±0.20     | 6.00 ±0.20 | 1.50 ±0.10 | 3.50 ±0.20 |
| 7   | RID3x3x5 H1.25        | 1   | 3.00 ±0.20     | 5.00 ±0.20 | 1.25 ±0.10 | 3.00 ±0.20 |
| 8   | RID3x5x5 H1.25        | 1   | 3.00 ±0.20     | 5.00 ±0.20 | 1.25 ±0.10 | 5.00 ±0.20 |
| 9   | RID3x6x4 H1.5         | 1   | 3.00 ±0.20     | 4.00 ±0.20 | 1.50 ±0.10 | 6.00 ±0.20 |
| 10  | RID3.5x5x6.5 H1.8     | 1   | 3.50 ±0.20     | 6.50 ±0.20 | 1.80 ±0.10 | 5.00 ±0.20 |
| 11  | RID3.8x10x6.9 H1.9    | 1   | 3.80 ±0.20     | 6.90 ±0.20 | 1.90 ±0.10 | 10.0 ±0.20 |
| 12  | RID4x6.2x7 H1.8       | 1   | 4.00 ±0.20     | 7.00 ±0.20 | 1.80 ±0.10 | 6.20 ±0.20 |
| 13  | RID4.1x4x6.6 H2.0     | 1   | 4.10 ±0.20     | 6.60 ±0.20 | 2.00 ±0.10 | 4.00 ±0.20 |
| 14  | RID4.1x6.6x7 H1.8     | 1   | 4.10 ±0.20     | 7.00 ±0.20 | 1.80 ±0.10 | 6.60 ±0.20 |
| 15  | RID5.358x9.4 H2.6     | 3   | 5.35 ±0.20     | 9.40 ±0.20 | 2.60 ±0.10 | 8.00 ±0.20 |
| 16  | RID6.5x4x12 H4.0      | 1   | 6.50 ±0.20     | 12.0 ±0.30 | 4.00 ±0.20 | 4.00 ±0.20 |
| 17  | RID7.4x14.7x13.4 H3.8 | 1   | 7.40 ±0.20     | 13.4 ±0.30 | 3.80 ±0.20 | 14.7 ±0.20 |
| 18  | RID7.5x4x13.5 H4.2    | 1   | 7.50 ±0.20     | 13.5 ±0.30 | 4.20 ±0.20 | 4.00 ±0.20 |
| 19  | RID7.5x7x13.3 H4.0    | 1   | 7.50 ±0.20     | 13.3 ±0.30 | 4.00 ±0.20 | 7.00 ±0.20 |
| 20  | RID8x7x15 H5.0        | 1   | 8.00 ±0.20     | 15.0 ±0.30 | 5.00 ±0.20 | 7.00 ±0.20 |

Copyright 2005 YUXIANG Magnetic Materials Ind. Co.,Ltd.All Rights Reserved.

Add:F16, Jinyuan plaza, # 57 South hubin, Xiamen, 361004 China.

Tel : (86)592 2295387 (86)592 2217138 Fax: (86)592 2207122

Email : magnetcom@gmail.com sales@magnet-tech.com